

Hisense model		HALO 12000
Combo		CBMR1205G+CBMR1205W
Ean		6926597731148/6926597731155
Performance		
Pdesign Cooling	W	3200
Pdesign Heating Average	W	2900
Pdesign Heating Warm	W	3200
SEER	Cooling	6,8
SCOP	Heatling Average	4
SCOP	Heatling Warm	5,1
Energy Class	Cooling	A++
Energy Class	Heatling Average	A+
Energy Class	Heatling Warm	A+++
Cooling Capacity	W	3200(1000-4000)
Heating Capacity	W	3300(1000-4200)
Input-Cooling	W	940(190-1600)
Input-Heating	W	845(190-1600)
Moisture Removal	L/H.r	1,2
Air Circulation (Indoor) (H/H-M/M/M-L/L)	m3/h	550
Air Circulation (Outdoor)	m3/h	2000
EER for Cooling	W/W	3,40
COP for Heating	W/W	3,90
Max current	A	7
Refrigerant		R32
Refrigerant charge volume	q	660
Indoor Unit Noise Level - Sound Power	dB (A)	57
Indoor Unit Noise Level - Sound Pressure	dB (A)	39/37/34/32/30/24
Outdoor Unit Noise Level - Sound Power	dB (A)	62
Outdoor Unit Noise Level - Sound Pressure	dB (A)	52
Annual energy consumption(cooling)	kWh/a	165
E	a	878
	average	1015
	colder	/
Power Supply		
Voltage, Frequency, Phase	V	220-240V~,50Hz,1P
Rated Current	Cooling (A)	4,2
	Heating (A)	3,8
System		
Compressor type		Rotary
Compressor Model No.		KSK89D59UEZC
Compressor MFG		GMCC
Expansion Device		Capillary
Evaporator		Copper tube and Aluminum Fin
Condenser		Copper tube and Aluminum Fin
Connecting Pipe Diameter		
Liquid Pipe	inch	1/4
Gas Pipe	inch	3/8
Features		
HI-NANO Sterilization		Optional
Fire Alarm/Room Card Port		Yes
Carbon Filter		Yes
Wifi APP Control		Optional

Voice Control (with Alexa Google)		Optional
Display on Front Panel		Yes
LCD Wireless Remote Controller		Yes
Removable and washable Panel		Yes
Washable PP Filter		Yes
24 Hours Timer		Yes
3 Speed and Auto Indoor Fan Control		Yes
Vertical Auto Swing Louver		Yes
Sleep Operation		Yes
Smart Function		Yes
Super Function		Yes
Auto Restart		Yes
Silent Mode		Yes
Dimmer		Yes
2 Ways Draining Connection (Left or Right)		Yes
Low ambient temperature cooling		Yes
Horizontal Auto Swing Louver		Yes
Super silence		Yes
8 degree celsius heating		Yes
5 Speed and Auto Indoor Fan Control		Yes
Other		
Net Dimensions WxHxD (mm)	Indoor Unit	790×255×197
	Outdoor Unit	780×540×260
Net Weight (Kg)	Indoor Unit	7.1
	Outdoor Unit	25
Packing Dimensions WxHxD (mm)	Indoor Unit	850×320×260
	Outdoor Unit	910×600×360
Gross Weight (Kg)	Indoor Unit	8.6
	Outdoor Unit	28
Loading Capacity (20'/40'/40'HC) No Pipe		112/222/264
Test Standard		EN 14511,EN 14825, EN 12102
Approvals		CE
Operating Temp Range (°C)	cooling	-15°C-43°C
	heating	-15°C-24°C
Max allowable tubing length at shipment	m	5
limit of tubing length	m	20
limit of elevation difference H	m	10
required amount of additional refrigerant	g/m	20

